

## STREET LIGHTING





## STRUCTURE, MATERIALS, FEATURES:

- \* High quality LED with excellent luminous efficiency
- \* Wide range light spread
- \* Use High efficiency driver
- \* Superior Quality Light
- \* Thermal conductivity Management
- \* No UV or IR radiation
- \* High quality Die-cast Aluminium alloy housing

| SPECIFICATION                     | STREET LIGHT              |
|-----------------------------------|---------------------------|
| Model Name                        | GJASS6DA                  |
| Power                             | 60 Watt                   |
| LED Type / Quantity               | 3535 3W Ceramic PKG       |
| Luminous Flux                     | 6,600 lm (Typ)            |
| Effesiency (Lumen/Watt)           | 110 lm/Watt               |
| LED Efikasi                       | 130 lm/Watt               |
| Light source                      | Modular (Can be Up grade) |
| Input supply voltage              | 110 - 277 VAC, 50 - 60Hz  |
| Power Driver for dimming          | 1 - 10 V                  |
| Driver                            | Meanwell                  |
| ССТ                               | 4,000K                    |
| CRI                               | ≥ 75                      |
| IP Rating for Optic space /Driver | IP65                      |
| LED Life Time                     | 50.000 Hours              |
| Warranty                          | 2 years                   |
| Housing Die                       | Cast Aluminium            |
| Dimension                         | 970 x 455 x 220 mm        |
| Weight                            | 10,000 g                  |











Manufactured: By PT. Sharp Semiconductor Indonesia

